

Lateral Feeders

Solutions Through Creative Innovation



- ◆ Efficiency Maximized with continuous lateral butt-feeding
- ◆ Cool and Quiet Operation with a pressure-compensating hydraulic system
- ◆ Quick Ratio Changes with independently adjustable speeds of lateral chain and feed drive rollers
- ◆ Chain Life Improved due to elevation of parts from four idler rollers
- ◆ Quick Height SetUp Changes with Electric Height Control
- ◆ Durable and Quiet UHMW lateral feed chains
- ◆ Heavy-Duty Integrated steel frame with Jack Legs
- ◆ PLC Controlled: 3 Modes-Manual/Auto/Single

Six-Wheel Bridge Feeder



THOMAS
MANUFACTURING

Ph: 620.724.6220
Fax: 620-724-4653
Email: info@thomasmanufacturing.com
www.thomasmanufacturing.com

Product Information

MACHINE OPERATION:

- 1) UHMW feed chains move parts laterally to polyurethane feed rollers
- 2) A photoeye detects a part which causes feed rollers to lower onto part propelling—butt-feeding—it into moulder
- 3) At the trailing end of the part, the feed rollers raise to allow the next part in. The cycle is repeated.

MACHINE SPECIFICATIONS: Specifications **vary** depending on model purchased.

Physical dimensions: *Table lengths available—60", 72", 96", 144", 168"
Number of chains—4, 5, 6, 7, 8, 9
*Table widths available—36", 48", 60", 96"
Height (adjustable) 30"-38"

Power—3-Phase, 230/460

Motors—Variable hydraulic

Standard material dimensions: Length— 16" Minimum
Width— 1" Minimum
Thickness— 0.25"-3"


OPTIONS:

Tilt feeding

Customized material dimensions

*Longer lengths & widths available

Dimensions &
Specifications Vary.



Distributed by: