

Interchangeable Torque Wrench 20~200 Nm

TW-200

The interchangeable torque wrench is supplied inside a protective case. Inside, in addition to the instruction manual, you'll find the calibration certificate (unique for each instrument) according to DIN ISO 6789 & ASME B107.300-2010.



Scale Adjuster

Torque Scale (Nm/Lbt-ft)

Interchangeable Head S=14x18mm

Optional



- TW-2836** (ER16 & ER20)
- TW-4045** (ER25)
- TW-5055** (ER32)
- TW-5862** (ER40 & EOC25)
- TW-8001** (Kinetic Dust Extractor 992)
- TW-1001** (Kinetic Dust Extractor 992)



TW-A912



TW-A095
TW-A127

TECHNICAL DETAILS:

- Range..... 20~200 Nm (10-150 lbf-ft)
- Resolution 1 Nm
- Tolerance..... ±4%
- Length 500mm (19.7")
- Weight..... 1,15Kg. (40.6oz)
- Automatic quick-release, audible and palpable click, when selected torque is reached
- Right-handed (CW)

TORQUE SUGGESTED*

CHUCK/COLLET	Nm	Lbf-ft
ER16	57	42
ER20	80	59
ER25	104	77
ER32	135	100
ER40	176	130
EOC25	122	90

* Suggested tightening torque for CMT Chuck/Collet

APPLICATION:



The interchangeable torque wrench is widely used in various fields but is suggested for the tightening of our chucks.

ORDER NO.		D mm	DESCRIPTION
TW-200		14x18	Interchangeable Torque Wrench 20~200 Nm
TW-2836		14x18	Hook Head Insert Ø=28-36mm (ER16 & ER20)
TW-4045		14x18	Hook Head Insert Ø=40-45mm (ER25)
TW-5055		14x18	Hook Head Insert Ø=50-55mm (ER32)
TW-5862		14x18	Hook Head Insert Ø=58-62mm (ER40 & EOC25)
TW-8001		14x18	Hook Head Insert Ø=80mm (Kinetic Dust Extractor 992)
TW-1001		14x18	Hook Head Insert Ø=100mm (Kinetic Dust Extractor 992)
TW-A095		14x18	Push Ratchet Insert S2=3/8"
TW-A127		14x18	Push Ratchet Insert S2=1/2"
TW-A912		14x18	Adapter Insert S2=9x12mm