

Forstner Bits



537



ORDER NO. Right-hand rotation	D inches	L inches	S inches	ORDER NO. Right-hand rotation	D mm	L mm	S mm
537.064.31	1/4	3-35/64	3/8	537.100.31	10	90	8
537.095.31	3/8	3-35/64	3/8	537.120.31	12	90	8
537.127.31	1/2	3-35/64	3/8	537.140.31	14	90	8
537.158.31	5/8	3-35/64	3/8	537.150.31	15	90	8
537.190.31	3/4	3-35/64	3/8	537.160.31	16	90	8
537.222.31	7/8	3-35/64	3/8	537.180.31	18	90	8
537.254.31	1	3-35/64	3/8	537.200.31	20	90	8
537.285.31	1-1/8	3-35/64	3/8	537.220.31	22	90	8
537.317.31	1-1/4	3-35/64	3/8	537.240.31	24	90	8
537.349.31	1-3/8	3-35/64	3/8	537.250.31	25	90	8
537.381.31	1-1/2	3-35/64	3/8	537.260.31	26	90	8
537.413.31	1-5/8	3-35/64	3/8	537.280.31	28	90	8
537.445.31	1-3/4	3-35/64	3/8	537.300.31	30	90	8
537.476.31	1-7/8	3-35/64	3/8	537.320.31	32	90	10
537.508.31	2	3-35/64	3/8	537.350.31	35	90	10
537.540.31	2-1/8	3-35/64	3/8	537.380.31	38	90	10
				537.400.31	40	90	10
				537.450.31	45	90	10
				537.500.31	50	90	10
				537.550.31	55	90	10
				537.680.31	68	159	12.5

TECHNICAL DETAILS:

- Super-strength steel SP steel
- Precision balanced center point - 2 spurs (V2)
- 2 precision ground cutting edges (Z2)
- Long lasting cutter performance.

APPLICATION: used to drill precise flat bottom holes with no chipping in any thickness of soft wood. For drilling holes in any direction and making arched openings. For drilling partially overlapped flat bottom holes for easy mortising. For drilling niches used to fix supports.