

DP spiral router cutters with shear angle



DP **Z3** **RH**

143



| D mm | I mm | L mm | S mm | Z | ORDER NO. Right-hand rotation |
|-----------------------------|---------|---------|---------|----------------|----------------------------------|
| 22 | 30 | 90 | 25x50 | 3 (12 DP+1 HW) | 143.220.61 |
| <input type="checkbox"/> 22 | 35 | 95 | 25x50 | 3 (15 DP+1 HW) | 143.221.61 |
| 22 | 40 | 100 | 25x50 | 3 (18 DP+1 HW) | 143.222.61 |
| <input type="checkbox"/> 22 | 45 | 105 | 25x50 | 3 (20 DP+1 HW) | 143.223.61 |
| 22 | 50 | 110 | 25x50 | 3 (21 DP+1 HW) | 143.224.61 |
| <input type="checkbox"/> 22 | 55 | 115 | 25x50 | 3 (24 DP+1 HW) | 143.225.61 |
| 22 | 60 | 120 | 25x50 | 3 (27 DP+1 HW) | 143.226.61 |
| <input type="checkbox"/> 22 | 65 | 125 | 25x50 | 3 (29 DP+1 HW) | 143.227.61 |
| <input type="checkbox"/> 22 | 70 | 130 | 25x50 | 3 (30 DP+1 HW) | 143.228.61 |

TECHNICAL DETAILS:

- Super strength steel
- DP cutting edge
- HW plunging tip for diagonal plunge-cutting (Z-axis tool entrance)
- Resharpenable cutter (max 6 times)
- Max feed speed 25 m/min

40X
LONGER LIFE
THAN CARBIDE

APPLICATION: to be used on all CNC routers for jointing, rabbeting, grooving, copying and dividing cuts of raw material, melamine and laminates, MDF, HPL and veneered panels.
High performance on pre-and finish-routing.

On request